

# BUILDING SURVEY INSPECTION EZ KIT



Tramex moisture meters are designed to locate elevated moisture & humidity conditions, which may be conducive to mold, microbial growth and wood destroying organisms. These damp conditions can often be hidden within or behind a material such as drywall and not obvious from visual inspection without the help of a non-destructive moisture meter. Once the moisture source is identified and stopped, remedial action can be taken leading to a healthier building environment. This complete moisture and humidity testing kit features the multifunctional Tramex MRH III digital moisture meter allowing for non-invasive testing of moisture conditions in numerous building materials such as drywall, wood, plaster, brick, ceramic tiles, resilient flooring, laminates and roofing. The MRH III and reusable Ambient Relative Humidity Hygro-i2 Short Probe allow for testing relative humidity, temperature and dew point in the environment. The heavy-duty pin-probes measure moisture content in wood, and the insulated 7" pins allow for deep wall cavity probing. Concrete slab relative humidity testing to ASTM F2170 can also be performed with reusable relative humidity probes and hole liners (optional).



## KIT CONTENTS

1. MRH III – moisture and humidity meter.
2. Ambient Relative Humidity Hygro-i2 Short Probe.
3. Heavy-duty pin-type wood probe.
4. 7" insulated pins for in-depth penetration using pin probe.
5. 8 x Ambient RH Probe Hole Liners.

Product Code: BSIZK5.1

## FEATURES OF MRH III

- Deep signal, non-destructive penetration up to 1 3/4" in wood and drywall in non-destructive mode.
- Detects moisture through paint, wall coverings, drywall, ceramic tiles, floor coverings, wood, roof coverings and most building materials.
- Hold function "freezes" meter reading when inspecting areas where the meter face is not visible.
- Audio signal sounds when meter indicates high readings.
- Large clear backlit digital display giving meaningful readings.
- Accurate non-invasive moisture content readings from 5 to 55% MC in wood.
- Attachable pin-type wood probe for accessing hard to reach areas and for probing into wall cavities and wood.
- Attachable Relative Humidity probe for testing of relative humidity, temperature, dew point and grains per pound readings all shown on one clear display, (as well as in situ of concrete per ASTM F2170 with optional Hygro-I probes, hole liners and caps).

## MEASURING RANGE - MRH III

Depth of penetration:	up to 1 3/4" (30mm) (in wood, drywall)
Reference scale for building materials	0 to 100
Relative Humidity (with RH probe)	0 to 99%
Humidity accuracy:	0% to 99%RH +/- 2% @ 25°C / 77°F
Wood Non-invasive Mode	5 to 55%MC (at SG of 0.3)
Wood Invasive Mode (with wood pin probes)	7 to 40%MC

## SPECIFICATIONS OF KIT

Size:	13.8" x 9.1" x 3.5" (350mm x 230mm x 90mm)
Weight:	3.4lbs (1.55kg)
Power:	1 x 9 volt PP3 Battery (included)



BSIZK5.1-US 09/18 REV.1.1



Non-destructive



Pin Probe



Ambient conditions