

# FEEDBACK DATA LOGGER STARTER KIT

TEMPERATURE AND RELATIVE HUMIDITY

FBSK5.1



## KIT CONTENTS:

- 1 x DL-RHTX Data Logger
- 1 x Hygro-i2 probe
- 1 x Wall mounting
- 1 x Tripod Stand



**Tramex Feedback  
DataLogger App**  
For use with Tramex  
DL-RHTA and DL-RHTX  
Dataloggers.

Available on:



The Tramex Feedback DataLogger and App have been designed and developed by Tramex for professionals who depend on accurate, reliable readings using the very best, state of the art technology and performing BS 8201, 8203, 5325 and ASTM F2170. The Feedback DataLogger and App log up to 100,000 data point entries for relative humidity, temperature, dew point and grains per pound, transmitted wirelessly via Bluetooth BLE technology to your mobile device. On the App you can visualise Live Readings, Thermal Conditions and Psychrometric Charts, as well as creating and exporting spreadsheets, charts and reports. The Tramex Feedback DataLogger requires the Tramex Feedback Data Logger App and a compatible iOS or Android mobile device.



Product order code: FBSK5.1

## FEATURES

- Bluetooth BLE enabled for use with mobile devices.
- Up to 100,000 data point entries possible.
- Instant set up and start modes.
- Used to perform BS 8201, 8203, 5325 and ASTM F2170.
- Ambient and In-situ RH and temperature logging
- Intuitive and instructive APP interface.
- Adjustable interactive chart, spreadsheet, report and easy-export functions.
- Connectivity up to 50 meters (165ft) for highly accessible data downloads.

**BS 8201, 8203, 5325 and ASTM F2170 COMPLIANT**



## SUPPORTED MEASUREMENTS

- Ambient Relative Humidity, Temperature, Dew point, Grains per pound.
- In Situ Relative Humidity, Temperature, Dew point, Grains per pound (with optional plug-in RH Probe)
- Contact Temperature, Estimated contact RH, Ambient Dew Point, Contact Delta Temperature (with optional contact Temperature Probe)
- Psychrometric chart showing Relative Humidity, Specific Volume, Wet Bulb Temperature, Dry Bulb Temperature, Enthalpy, Humidity Ratio, Dew Point.

## DATALOGGER SPECIFICATIONS

With built-in Ambient RH + Temperature sensor; Plug-in RH + Temperature Sensor (optional); Contact Temperature Probe (optional) providing the best available accuracy tolerances of 1.5%RH & 0.1°C.

<b>Size:</b>	100mm x 90mm x 35mm (3.94" x 3.54" x 1.38")
<b>Weight:</b>	100g (3.53oz)
<b>Construction:</b>	ABS enclosure
<b>Power:</b>	1 x AA type battery 1.5 Volt
<b>Memory:</b>	100,000 data point entries (samples of Ambient RH and temperature; Surface Temperature)
<b>Logging Rate:</b>	Logger interval adjustable between 5 minutes and 1 hour
<b>Transmission Range:</b>	Up to 50m (165ft) line-of-sight
<b>Bluetooth:</b>	BLE Bluetooth Low Energy 4.2 compliant, Bluetooth 5 advertising
<b>Included:</b>	Wall Mounting and Tripod Stand

## HUMIDITY AND TEMPERATURE SPECIFICATIONS

### RELATIVE HUMIDITY SENSOR SPECIFICATIONS:

<b>Range:</b>	0 to 100%RH
<b>Accuracy:</b>	±1.5%RH Range 0% to 80%RH ±2.0%RH Range 80% to 99%RH (@25°C (77°F))
<b>Resolution:</b>	0.1% over the complete range
<b>Drift:</b>	<0.25%RH per year


### TEMPERATURE SENSOR SPECIFICATIONS:

<b>Range:</b>	-40°C to 125°C (-40°F to 257°F)
<b>Accuracy:</b>	±0.1 °C Range 20°C to 60°C (±0.1°F Range 68°F to 140°F)
<b>Sensor Protection:</b>	PTFE Film protects sensor opening from water & dust
<b>Drift:</b>	<0.03°C (0.04°F) per year


## CONTACT TEMPERATURE PROBE (OPTIONAL)

<b>Units:</b>	°C (°F)
<b>Temperature Range:</b>	-30°C to +80°C (-20°F to +175°F)
<b>Accuracy:</b>	±0.5°C from -10°C to +85°C (±0.9°F from 14°F to 185°F)
<b>Resolution:</b>	0.1% over the complete range


Live Readings



Thermal Condition



Psychrometric Chart



Available Devices



## BATTERY

**Power supply:** 1 x AA type battery 1.5 Volt

**Battery life:** Over 1 year based on logging intervals of 5mins, using an alkaline battery with a nominal voltage of 1.5V as supplied.

## CERTIFICATION

CE: EN 61326-1

FCC: Part 15-J

ROHS Compliant

