

FLOORING INSPECTION EZ KIT



A compact kit for instant and precise moisture testing of wood flooring, concrete and other floor screeds. The Tramex CMEX II digital moisture meter allows the user to non-invasively test concrete per international standard ASTM F2659 and for testing relative humidity, temperature and dew point in the environment, or performing in situ and hood testing (with optional hood) of relative humidity in concrete slabs to international standards BS 8201, 8203, 5325 and ASTM F2170. The Tramex heavy-duty wood pin-probe measures the moisture content of wood. The Flooring Inspection EZ Kit comes in a Tramex Easy-travel case.



KIT CONTENTS

1. CMEX II - concrete meter.
2. 1 x Hygro-i2® Relative Humidity probe.
3. 6 x Hole liners.
4. Heavy-duty pin-type wood probe.

Product Code: FZK5.2

FEATURES OF CMEX II

- Measures up to 6.9% Moisture Content in concrete.
- Carbide Method (CM) equivalent scale for concrete.
- Large clear backlit digital display.
- Hold function "freezes" meter reading when inspecting areas where the meter face is not visible.
- Attaches to a relative humidity Hygro-i2® probe for testing of ambient conditions and in situ and hood testing of concrete (hood optional).
- 7% to 40% Moisture Content measurement in wood using Pin-type probe attachment.

MEASURING RANGE

Depth of penetration in concrete: (NDT*)	approx. 20 mm (¾")
Moisture content for concrete: (NDT*)	0 to 6.9 %
Carbide Method Equivalent for concrete:	0 to 4.3
Reference scale: (NDT*)	0 to 100
Moisture Content in wood using Pin Probe:	7 to 40%
Relative Humidity with Hygro-i2® probe:	0 to 99%
Humidity accuracy:	0% to 99%RH +/- 2% @ 25°C / 77°F

*NDT - Non-destructive Test

SPECIFICATIONS OF KIT

Size:	350mm x 230mm x 90mm (13.8" x 9.1" x 3.5")
Weight:	1.55kg (3.4lbs)
Power:	2 x 9 volt PP3 Batteries (included)



FZK5.2-EU 08/18 REV.1.1



ASTM F2659



ASTM F2170 & BS 8201