

# **MOISTURE ENCOUNTER**



**QUICK START GUIDE** 

## **OPERATION**

- Press U to switch ON/OFF.
- Press to select the required mode/scale.
- Press Moisture Encounter fully against the surface of the material.
- Readings are instant and displayed on analog dial.



- Last scale used is memorized when power is shut down and automatically selected next time unit is powered up.
- Hold/freeze: Press ① once. In HOLD mode the Hold LED will flash continuously. Press ② again to release hold. (If powered down while on Hold, the Moisture Encounter will retain information until powered up and hold is pressed again to release)
- Turn Audio signal on or off by pressing HOLD/AUDIO twice in quick succession.
- Automatic power timeout (5 mins) conserves battery life.

# **SCALES**

 Upper scale (5-30) indicates moisture content (MC%) of wood when used on wood products.



 Lower Scale (0-100) is a comparative scale and may be used for recording and comparing moisture condition in materials other than wood.

#### **DUAL-DEPTH PENETRATION**

- Shallow depth up to 0.40" (10mm)
- Deep depth up to 1.25" (30mm)

# MATERIALS AND SCALE SELECTION

- The ME5 has 5 ranges of sensitivity:
  - Wood & Timber
  - Shallow Depth
  - Drywall & Roofing
  - Plaster & Tile
  - Masonry

# **BLUETOOTH**

#### CALIBRATION & WARRANTY

- Obtain Warranty online: tramexmeters.com/register
- Annual calibrations are recommended as best practice. Calibration Check Boxes can be purchased for regular checks.

### **TROUBLESHOOTING**

- All LEDs flashing when unit is powered up.
  - Batteries are low and will soon need to be replaced.
- Single LED flashing and meter frozen.
  - Moisture Encounter is in HOLD mode.
  - Press HOLD button to release.

# **USER GUIDE ONLINE**

Please use the following link or QR code to access the complete User Guide online: http://l.ead.me/bb3OyA



Free App Available for Mobile and Tablet:





LI-ME5QSG

